## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

 (currently amended) Integrated multispot satellite communication system in a multimedia broadcasting network with a return channel, comprising;

a satellite that receives a multimedia broadcast signal from a provider and transmits said multimedia broadcast signal to a user in response to a request from said user;

common means of burst synchronisation such that the transmission rate in a downlink direction from the satellite is a whole multiple of a clock reference of said network; and

a network controller that receives different return channels from said user and said provider, via said satellite, wherein a signalling part of said multimedia broadcast signal is addressed from said provider to said network controller.

- (currently amended) The system according to claim 1, said system comprising awherein said satellite is configured to generate said network clock reference.
  - 3. (Previously Presented) The system of claim 2, further comprising a multiplexer.

- 4. (currently amended) The system according to claim 3, characterised in that said multiplexer is suitable for fittinginserts in a synchronous manner different uplink channels from the service provider and the user into a downlink signal, wherein a period of the downlink frame is equal to a period of the uplink frame.
- (currently amended) Method of burst synchronisation in an integrated multispot satellite communication system in a multimedia broadcasting network with return channel, comprising:

a network controller receiving different return channels from a user and a provider, via a satellite, wherein a signalling part of a multimedia broadcast signal from said provider to said user, in response to a user request, is addressed from said provider to said network controller,

wherein said synchronisation is common for a multimedia services provider and a user, in such a manner that the transmission rate in a downlink direction is a whole multiple of a network clock reference.

- (currently amended) The method according to claim 5, comprising generating said network clock reference in [[a]]said satellite of said system.
- (currently amended) The method of claim 5, wherein [[a]]said satellite uses a
  multiplexer to perform said synchronization.

U.S. Application Serial No. 09/986,555 Attorney Docket No.: Q66984 Amendment under 37 CFR 1.111

8. (Previously Presented) The method of claim 7, wherein said multiplexer synchronously fits different uplink channels into a downlink signal, and a period of the downlink frame is equal to a period of the uplink frame.

- (Previously Presented) The system of claim 1, wherein said system is configured to communicate in accordance with digital video broadcasting-return channel system (DVB-RCS).
- (Previously Presented) The method of claim 5, wherein method comprises communicating in accordance with digital video broadcasting-return channel system (DVB-RCS).
- (Previously Presented) The system of claim 1, wherein said downlink direction transmission rate is one of 54 Mbit/s. 81 Mbit/s and 108 Mbit/s.
- (Previously Presented) The method of claim 5, wherein said downlink direction transmission rate is one of 54 Mbit/s. 81 Mbit/s and 108 Mbit/s.
- (Previously Presented) The system of claim 1, wherein a bandwidth of a transmitter onboard said satellite is a multiple of 27 MHz.

 (Previously Presented) The method of claim 5, wherein a transmitter onboard said satellite operates at a bandwidth that is a multiple of 27 MHz.

## 15. (New) The system of claim 1, further comprising:

a regenerator, positioned on said satellite, that performs multiplexing and at least one of cross-connecting and broadcasting channels to different coverage zones, wherein said network controller performs control operations and verifies at least one of an identity and a profile of said user.

- 16. (New) The method of claim 5, further comprising performing multiplexing and at least one of cross-connecting and broadcasting channels to different coverage zones, by a regenerator positioned on said satellite, wherein said network controller performs control operations and verifies at least one of an identity and a profile of said user.
- (New) The system of claim 1, wherein said request from said user comprises a request for video on demand service.
- (New) The method of claim 5, wherein said request comprises a request for video on demand service.